

Features:

- Fiber Optic Enclosure, Dome type
- Made of high-density engineering plastic
- Intergrated seal, air tight and water proof.
- Can be used in straight-through or branch splice locations
- Meet top telecommunication quality
- Easy to re-enter
- Ideal for cable repair
- Suitable for aerial, underground duct or direct burial applications



FT-S004H

Specification:

- L×W×H : 435mm×190mm×120mm
- Cable ports : 4 ports (2 ports in, 2 ports out)
- Cable Diameter: ϕ 10mm~ ϕ 22mm
- Max. Capacity : 24F~192F
- Core capacity per tray: 24F
- Holds up to 8 trays
- Suitable for duct, aerial, direct buried application



FT-S001H

Specification:

- L×W×H : 400mm×200mm×120mm
- Cable ports : 6 ports
- Cable Diameter: ϕ 13mm~ ϕ 16mm
- Max. Capacity : 12F~96F
- Core capacity per tray: 12F or 24F
- Holds up to 4 trays
- Suitable for duct, aerial, direct buried application



FT-S002H

Specification:

- L×W×H : 323mm×202mm×86mm
- Cable ports : 6 ports
- Cable Diameter: ϕ 20mm (Max.)
- Max. Capacity : 12F~96F
- Core capacity per tray: 12F or 24F
- Holds up to 4 trays
- Suitable for duct, aerial, direct buried application



FT-S003H

Specification:

- L×W×H : 280mm×200mm×90mm
- Cable ports : 2 ports
- Cable Diameter: ϕ 14mm (Max.)
- Max. Capacity : 12F~96F
- Core capacity per tray: 12F or 24F
- Holds up to 4 trays
- Suitable for duct, aerial, direct buried application