

Features:

- Suitable for small capacity fiber communication engineering
- Standard 12-fiber splicing tray, which is convenient for off-frame operation
- Provision of function such as splicing, termination, as well as direct-connection of fibers
- Clear identification for connection and termination of each fiber in cabinet
- Adapter port: SC/ST/FC available
- Fiber capacity: 12/24 cores
- Operating Temperature: - 25C~70C
- Storage Temperature: -25C~85C
- Relative Humidity: <85~+30C
- Air pressure: 70Kpa~106Kpa

Application:

- Optic Access Network
- Local Area Network
- FTTH
- Telecommunication



**FOT-FWB03-24A
(Double Door)**

Standard Accessories:

- Splice Tray(12 core or 24 core available)
- Heat sleeves
- Adapter plate
- Cable gland
- Cable Tie
- Cage nut
- Cable organizer
- Installing Screws



**FOT-FWB01-24
(Double Door)**



Folded

Order Information:

P/N	Dimension(mm)	Fiber Port	Max. Capacity(core)	Adapter Option
FT-FWB01-12	305*305*30	SC Simplex	12	SC/FC/LC/ST
FT-FWB01-24	400*405*80	SC Simplex	24	SC/FC/LC/ST
FT-FWB01-48	400*300*120	SC Simplex	24	SC/FC/LC/ST
FT-FWB03-24A	385*385*115	SC Simplex	24	SC/FC/LC/ST
FT-FWB03-48A	385*385*115	SC Simplex	24	SC/FC/LC/ST