

Product Information:

- Comply with ANSI/EIA; RS-310-D; DIN41491; IEC297-2; DIN41494; GB/T3047.2-92 standard
- Compatible with 19 international standard, meric system and ETSI standard
- Supplied as a flat pack-easy to assemble, only 1/3 of original assembled volume
- Specialized cable shunting parts with easy entry
- Cable can ne entered from top and bottom, dust and sundries can be prevented by dust-proof sponge
- Cooling fans can be installed on top cover and bottom panel
- Toughened glass front door with over 180 turning degrees

Product Characteristic:

- Static loading: 60KG
- Surface finish: digressing, pickling, phosphoric, power coated Material: SPCC cold rolled Steel
- Thickness: Frame, mounting profile: 1.5mm, front door border: 1.2mm, others: 0.8mm
- Color:RAL9005(black) RAL7044(grey)



Ordering Information:

Part Number	Width*Depth*Height(mm)	Capacity(U)
FT-WMC6406	600*450*368	6
FT-WMC6606	600*600*368	
FT-WMC6409	600*450*501	9
FT-WMC6609	600*600*501	
FT-WMC6412	600*450*635	12
FT-WMC6612	600*600*635	
FT-WMC6415	600*450*769	15
FT-WMC6615	600*600*769	
FT-WMC6418	600*450*901	18
FT-WMC6618	600*600*901	
FT-WMC6422	600*550*1082	22
FT-WMC6622	600*600*1082	



www.aldahiyah.com sales@aldahiyah.com