

All components of / and the final products are designed and tested to conform the requirements of IEC 60874-7 CECC 86115-801, Bellcore / Telcordia GR-326, EIA/TIA 604-3A, EIA/TIA 568, ISO/IEC 11801 2nd Ed., EN 50173, JIS C5973 F04, ICEA-596, IEC60793-2-10 A1aITU-T G. 651 or IEC60793-2-10 A1b or ITU-T G.652 (depending on fiber), Belcore / Telcordia GR-409-CORE,IEC 793, IEC 794-1-E1, IEC 794-1-E3, UL1666/901 (UL-cable) and EIA/TIA455.

Applications:

- CATV
- Telecommunication networks
- Local Area Networks(LANs)
- Metro networks
- Data processing networks
- Industrial ,military and medical

Features:

- Compliant with TIA-568-B.3 performance requirements
- Terminable with commonly available tools
- Fiber Compatibility:9/125um, 62.5/125um, 50/125um
- Low insertion loss: ≤0.2dB (Typical ≤0.1dB)
- High return loss
- 5- 30dB available

Plug-in Fixed Type

P/N	Description
FT-TPSCS10	SC/PC Singlemode 10dB
FT-TPSCS15	SC/PC Singlemode 15dB
FT-TPFCS10	FC/PC Singlemode 10dB
FT-TPFCS15	FC/PC Singlemode 15dB



SC/PC SM



FC/PC SM

P/N	Description
FT-TPSTS10	ST/PC Singlemode 10dB
FT-TPSTS15	ST/PC Singlemode 15dB
FT-TPLCS10	LC/PC Singlemode 10dB
FT-TPLCS15	LC/PC Singlemode 15dB



ST/PC SM



LC/PC SM

Adapter Fixed Type

P/N	Description
FT-TASCSA10	SC/APC Singlemode 10dB
FT-TASCSA15	SC/APC Singlemode 15dB
FT-TASCS10	SC/PC Singlemode 10dB
FT-TASCS15	SC/PC Singlemode 15dB



SC/APC SM



SC/PC SM

P/N	Description
FT-TVFCS10	FC/PC Singlemode 10dB, Variable type
FT-TVFCS15	FC/PC Singlemode 15dB, Variable type
FT-TAFCS10	FC/PC Singlemode 10dB, Adapter fixed type
FT-TAFCS15	FC/PC Singlemode 15dB, Adapter fixed type



FC/PC SM



FC/PC SM