



FOT-PP01



Changeable Adapter Plate

Features:

- 1U 19" rack patch panel, sliding type
- Available for SC,ST,FC,LC Adapter, simplex & duplex
- The case body is made from cold rolled steel sheet
- 3 Piece front panels can be changeable upon request
- Max. output fibers: 48 core
- Dimension: 482mm*230mm*45mm(1U)
- Color available: Black

Performance:

- Operating Temperature: - 25° C ~70° C
- Storage Temperature: - 25° C ~85° C
- Relative Humidity: ≤85% ~ +30° C
- Atmosphere pressure: 70Kpa ~ 106Kpah
- Fiber Bending Radius : ≥40mm

1U & 2U 19" Rack Patch Panel

Features:

- 1U 19" rack patch panel, fixed type
- Available for SC,ST,FC,LC Adapter, simplex & duplex
- The case body is made from cold rolled steel sheet
- 3 Piece front panels can be changeable upon request
- Max. output fibers: 48 core
- Dimension: 482mm*250mm*1U
- Color Available: Black

Performance:

- Operating Temperature: - 25° C ~70° C
- Storage Temperature: - 25° C ~85° C
- Relative Humidity: ≤85% ~ +30° C
- Atmosphere pressure: 70Kpa ~ 106Kpah
- Fiber Bending Radius : ≥ 40mm



FOT-PP02



FOT-PP02

1U 19" Rack Patch Panel

Features:

- 19" standard size, fixed type
- Available for SC,ST,FC,LC Adapter, simplex & duplex
- The case body is made from cold rolled steel sheet
- Max. output fibers: 48 core
- Color available: Gray/Black



FOT-PP03

Order Information:

P/N	Dimension(mm)	Fiber Port	Max. Capacity(core)	Adapter
FT-PP01-12SC	482×230×1U	3*SC Simplex	12	SC Simplex
FT-PP01-12ST	482×230×1U	3*ST Simplex	12	ST Simplex
FT-PP01-24SC	482×230×1U	3*SC Simplex	12	SC Simplex
FT-PP01-48SC	482×230×1U	3*SC Duplex	48	SC Duplex
FT-PP02-24ST	480×250×1U	24ST Simplex	24	ST Simplex
FT-PP02-48SC	480×250×2U	48SC Simplex	48	SC Simplex
FT-PP03-24SC	430×300×1U	24SC Duplex	48	SC Duplex